




Ausf. 6F




Ausf. 6WF



Ausf. 6A



Ausf. 10WF



Ausf. 10A

Bezeichnung	Anzahl der Zähne	Ausführung	Material	D _p (mm)	D _e (mm)	D _f (mm)	F (mm)	L (mm)	D _m (mm)	D _i (mm)	Vorbohrung d (mm)	Fertigbohrung d _{max} (mm)
8M - Teilung 8 mm für Riemenbreite 20 mm												
22 8M 20	22	6F	ST	56,02	54,65	60	28	38	43	-	12	30
24 8M 20	24	6F	ST	61,12	59,75	66	28	38	45	-	12	30
26 8M 20	26	6F	ST	66,21	64,84	70	28	38	48	-	12	35
28 8M 20	28	6F	ST	71,30	70,08	75	28	38	50	-	15	35
30 8M 20	30	6F	ST	76,39	75,13	83	28	38	55	-	15	35
32 8M 20	32	6F	ST	81,49	80,16	87	28	38	60	-	15	40
34 8M 20	34	6F	ST	86,58	85,22	91	28	38	70	-	15	45
36 8M 20	36	6F	ST	91,67	90,30	97	28	38	75	-	15	45
38 8M 20	38	6F	ST	96,77	95,39	102	28	38	75	-	15	45
40 8M 20	40	6F	ST	101,86	100,49	106	28	38	75	-	15	45
44 8M 20	44	6F	ST	112,05	110,67	120	28	38	75	-	15	45
48 8M 20	48	6F	ST	122,23	120,86	127	28	38	75	-	15	45
56 8M 20	56	6WF	ST	142,60	141,23	150	28	38	80	116	15	45
64 8M 20	64	6WF	ST	162,97	161,60	168	28	38	80	137	15	45
72 8M 20	72	6WF	ST	183,35	181,97	192	28	38	80	158	15	45
80 8M 20	80	6W	GG	203,72	202,35	-	28	38	90	180	15	50
90 8M 20	90	6A	GG	229,18	227,81	-	28	38	90	204	15	50
112 8M 20	112	6A	GG	285,21	283,83	-	28	38	90	254	18	50
144 8M 20	144	6A	GG	366,69	365,32	-	28	38	90	336	20	50
168 8M 20	168	6A	GG	427,81	426,44	-	28	38	100	400	20	55
192 8M 20	192	6A	GG	488,92	487,55	-	28	38	100	460	20	55
8M - Teilung 8 mm für Riemenbreite 30 mm												
22 8M 30	22	6F	ST	56,02	54,65	60	38	48	43	-	12	30
24 8M 30	24	6F	ST	61,12	59,75	66	38	48	45	-	12	30
26 8M 30	26	6F	ST	66,21	64,84	70	38	48	48	-	12	35
28 8M 30	28	6F	ST	71,30	70,08	75	38	48	50	-	15	35
30 8M 30	30	6F	ST	76,39	75,13	83	38	48	55	-	15	35
32 8M 30	32	6F	ST	81,49	80,16	87	38	48	60	-	15	40
34 8M 30	34	6F	ST	86,58	85,22	91	38	48	70	-	15	45
36 8M 30	36	6F	ST	91,67	90,30	97	38	48	75	-	15	45
38 8M 30	38	6F	ST	96,77	95,39	102	38	48	75	-	15	45
40 8M 30	40	6F	ST	101,86	100,49	106	38	48	75	-	15	45
44 8M 30	44	6F	ST	112,05	110,67	120	38	48	75	-	15	45
48 8M 30	48	6F	ST	122,23	120,86	128	38	48	75	-	15	45
56 8M 30	56	6WF	ST	142,60	141,23	150	38	48	90	116	15	50
64 8M 30	64	6WF	ST	162,97	161,60	168	38	48	90	137	15	50
72 8M 30	72	6WF	ST	183,35	181,97	192	38	48	95	158	15	50
80 8M 30	80	6W	GG	203,72	202,35	-	38	48	100	180	15	55
90 8M 30	90	6A	GG	229,18	227,81	-	38	48	100	204	15	55
112 8M 30	112	6A	GG	285,21	283,83	-	38	48	100	254	18	55
144 8M 30	144	6A	GG	366,69	365,32	-	38	48	100	336	20	55
168 8M 30	168	6A	GG	427,81	426,44	-	38	48	100	400	20	55
192 8M 30	192	6A	GG	488,92	487,55	-	38	48	100	460	20	55

Bezeichnung	Anzahl der Zähne	Ausführung	Material	D _p (mm)	D _e (mm)	D _i (mm)	F (mm)	L (mm)	D _m (mm)	D _i (mm)	Vorbohrung d (mm)	Fertigbohrung d _{max} (mm)	Gewicht (=kg)
8M - Teilung 8 mm für Riemenbreite 50 mm													
22 8M 50	22	6F	ST	56,02	54,65	60	60	70	43	-	12	30	1,000
24 8M 50	24	6F	ST	61,12	59,75	66	60	70	45	-	12	30	1,200
26 8M 50	26	6F	ST	66,21	64,84	70	60	70	48	-	15	35	1,500
28 8M 50	28	6F	ST	71,30	70,08	75	60	70	50	-	15	35	1,670
30 8M 50	30	6F	ST	76,39	75,13	83	60	70	55	-	15	35	1,970
32 8M 50	32	6F	ST	81,49	80,16	87	60	70	60	-	15	40	2,270
34 8M 50	34	6F	ST	86,58	85,22	91	60	70	70	-	15	45	2,690
36 8M 50	36	6F	ST	91,67	90,30	97	60	70	75	-	15	45	2,970
38 8M 50	38	6F	ST	96,77	95,39	102	60	70	75	-	15	45	3,230
40 8M 50	40	6F	ST	101,86	100,49	106	60	70	75	-	18	45	3,500
44 8M 50	44	6F	ST	112,05	110,67	120	60	70	75	-	18	45	3,900
48 8M 50	48	6F	ST	122,23	120,86	128	60	70	75	-	18	45	4,300
56 8M 50	56	10WF	ST	142,60	141,23	150	60	60	80	116	18	50	5,000
64 8M 50	64	10WF	ST	162,97	161,60	168	60	60	80	137	18	55	5,600
72 8M 50	72	10WF	ST	183,35	181,97	192	60	60	80	158	18	55	6,800
80 8M 50	80	10W	GG	203,72	202,35	-	60	60	110	180	18	60	6,900
90 8M 50	90	10A	GG	229,18	227,81	-	60	60	110	204	18	60	8,600
112 8M 50	112	10A	GG	285,21	283,83	-	60	60	110	254	18	60	9,600
144 8M 50	144	10A	GG	366,69	365,32	-	60	60	110	336	20	60	13,800
168 8M 50	168	10A	GG	427,81	426,44	-	60	60	120	400	20	65	16,000
192 8M 50	192	10A	GG	488,92	487,55	-	60	60	130	460	20	70	22,400
8M - Teilung 8 mm für Riemenbreite 85 mm													
22 8M 85	22	6F	ST	56,02	54,65	60	95	105	43	-	12	30	1,550
24 8M 85	24	6F	ST	61,12	59,75	66	95	105	45	-	12	30	1,900
26 8M 85	26	6F	ST	66,21	64,84	70	95	105	50	-	15	35	2,250
28 8M 85	28	6F	ST	71,30	70,08	75	95	105	50	-	15	35	2,550
30 8M 85	30	6F	ST	76,39	75,13	83	95	105	55	-	15	35	3,000
32 8M 85	32	6F	ST	81,49	80,16	87	95	105	60	-	15	40	3,570
34 8M 85	34	6F	ST	86,58	85,22	91	95	105	70	-	15	45	4,000
36 8M 85	36	6F	ST	91,67	90,30	97	95	105	70	-	15	45	4,500
38 8M 85	38	6F	ST	96,77	95,39	102	95	105	75	-	15	45	4,900
40 8M 85	40	6F	ST	101,86	100,49	106	95	105	75	-	18	45	5,200
44 8M 85	44	6F	ST	112,05	110,67	120	95	105	75	-	18	45	6,600
48 8M 85	48	6F	ST	122,23	120,86	128	95	105	80	-	18	45	7,600
56 8M 85	56	6F	ST	142,60	141,23	150	95	105	80		18	50	9,800
64 8M 85	64	10WF	ST	162,97	161,60	168	95	95	100	137	20	55	10,400
72 8M 85	72	10WF	ST	183,35	181,97	192	95	95	110	158	20	60	11,400
80 8M 85	80	10W	GG	203,72	202,35	-	95	95	110	180	20	60	11,100
90 8M 85	90	10A	GG	229,18	227,81	-	95	95	110	204	20	60	13,200
112 8M 85	112	10A	GG	285,21	283,83	-	95	95	110	254	24	60	16,300
144 8M 85*	144	10A	GG	366,69	365,32	-	95	95	120	336	24	65	21,500
168 8M 85*	168	10A	GG	427,81	426,44	-	95	95	120	400	24	65	26,100
192 8M 85*	192	10A	GG	488,92	487,55	-	95	95	130	460	24	70	30,600

AL = Aluminium ST = Stahl GG = Grauguss **Fertigungstechnische Änderungen vorbehalten.** * Keine Lagerware.