


Ausf. 6



Ausf. 6F

Bezeichnung	Anzahl der Zähne	Ausführung	Material	D _p (mm)	D _s (mm)	D _f (mm)	L (mm)	F (mm)	D _m (mm)	Vorbohrung d (mm)	Fertigbohrung d _{max} (mm)	Gewicht (≈kg)
AT10 - Teilung 10 mm für Riemenbreite 16 mm												
31 AT10 / 15-2	15	6F	AL	47,75	45,90	51	31	21	31	8	18	0,116
31 AT10 / 16-2	16	6F	AL	50,93	49,05	54	31	21	35	8	20	0,134
31 AT10 / 18-2	18	6F	AL	57,29	55,45	60	31	21	40	8	22	0,167
31 AT10 / 19-2	19	6F	AL	60,48	58,60	66,5	31	21	44	8	22	0,184
31 AT10 / 20-2	20	6F	AL	63,66	61,80	66,5	31	21	46	8	24	0,208
31 AT10 / 22-2	22	6F	AL	70,03	68,15	75	31	21	52	8	28	0,253
31 AT10 / 24-2	24	6F	AL	76,39	74,55	83	31	21	58	8	30	0,288
31 AT10 / 25-2	25	6F	AL	79,58	77,70	83	31	21	60	8	30	0,310
31 AT10 / 26-2	26	6F	AL	82,76	80,90	87	31	21	60	8	30	0,357
31 AT10 / 27-2	27	6F	AL	85,95	84,10	91	31	21	60	8	30	0,364
31 AT10 / 28-2	28	6F	AL	89,13	87,25	93	31	21	60	8	30	0,401
31 AT10 / 30-2	30	6F	AL	95,49	93,65	97	31	21	60	8	30	0,441
31 AT10 / 32-2	32	6F	AL	101,86	100,00	106	31	21	65	10	32	0,493
31 AT10 / 36-2	36	6F	AL	114,59	112,75	119	31	21	70	10	35	0,623
31 AT10 / 40-2	40	6F	AL	127,32	125,45	131	31	21	80	10	40	0,767
31 AT10 / 44-0	44	6	AL	140,06	138,20	-	31	21	88	10	46	0,993
31 AT10 / 48-0	48	6	AL	152,78	150,95	-	31	21	95	16	48	1,090
31 AT10 / 60-0	60	6	AL	190,98	189,10	-	31	21	110	16	60	1,710
AT10 - Teilung 10 mm für Riemenbreite 25 mm												
40 AT10 / 15-2	15	6F	AL	47,75	45,90	51	40	30	31	8	18	0,152
40 AT10 / 16-2	16	6F	AL	50,93	49,05	54	40	30	35	8	20	0,176
40 AT10 / 18-2	18	6F	AL	57,29	55,45	60	40	30	40	8	22	0,224
40 AT10 / 19-2	19	6F	AL	60,48	58,60	66,5	40	30	44	8	22	0,247
40 AT10 / 20-2	20	6F	AL	63,66	61,80	66,5	40	30	46	8	24	0,276
40 AT10 / 22-2	22	6F	AL	70,03	68,15	75	40	30	52	8	28	0,337
40 AT10 / 24-2	24	6F	AL	76,39	74,55	83	40	30	58	8	30	0,392
40 AT10 / 25-2	25	6F	AL	79,58	77,70	83	40	30	60	8	30	0,422
40 AT10 / 26-2	26	6F	AL	82,76	80,90	87	40	30	60	8	30	0,477
40 AT10 / 27-2	27	6F	AL	85,95	84,10	91	40	30	60	8	30	0,536
40 AT10 / 28-2	28	6F	AL	89,13	87,25	93	40	30	60	8	30	0,540
40 AT10 / 30-2	30	6F	AL	95,49	93,65	97	40	30	60	8	30	0,640
40 AT10 / 32-2	32	6F	AL	101,86	100,00	106	40	30	65	10	32	0,693
40 AT10 / 36-2	36	6F	AL	114,59	112,75	119	40	30	70	10	35	0,873
40 AT10 / 40-2	40	6F	AL	127,32	125,45	131	40	30	80	10	40	1,067
40 AT10 / 44-0	44	6	AL	140,06	138,20	-	40	30	88	10	46	1,350
40 AT10 / 48-0	48	6	AL	152,78	150,95	-	40	30	95	16	48	1,516
40 AT10 / 60-0	60	6	AL	190,98	189,10	-	40	30	110	16	60	2,339
AT10 - Teilung 10 mm für Riemenbreite 32 mm												
47 AT10 / 18-2	18	6F	AL	57,29	55,45	60	47	37	40	10	22	0,253
47 AT10 / 19-2	19	6F	AL	60,48	58,60	66,5	47	37	44	10	22	0,286
47 AT10 / 20-2	20	6F	AL	63,66	61,80	66,5	47	37	46	12	24	0,322
47 AT10 / 22-2	22	6F	AL	70,03	68,15	75	47	37	52	12	28	0,393
47 AT10 / 24-2	24	6F	AL	76,39	74,55	83	47	37	58	12	30	0,475
47 AT10 / 25-2	25	6F	AL	79,58	77,70	83	47	37	60	12	30	0,527

[illegible]