




Ausf. 6F



Ausf. 6A



Ausf. 6W



Ausf. 6WF

Bezeichnung	Anzahl der Zähne	Ausführung	Material	D _p (mm)	D _e (mm)	D _i (mm)	F (mm)	L (mm)	D _m (mm)	D _i (mm)	Vorbereitung d (mm)	Fertigbohrung d _{max} (mm)	Gewicht (≈kg)
L - Teilung 9,525 mm für Riemenbreite 050													
10 L 050	10	6F	ST	30,32	29,56	37	19	28	20	-	8	13	0,110
12 L 050	12	6F	ST	36,38	35,62	43	19	30	24	-	8	17	0,190
13 L 050	13	6F	ST	39,41	38,65	44	19	30	28	-	8	19	0,210
14 L 050	14	6F	ST	42,45	41,68	48	19	30	28	-	8	20	0,250
15 L 050	15	6F	ST	45,48	44,72	51	19	30	34	-	8	23	0,300
16 L 050	16	6F	ST	48,51	47,75	54	19	32	36	-	8	23	0,330
17 L 050	17	6F	ST	51,54	50,78	57	19	32	36	-	10	24	0,360
18 L 050	18	6F	ST	54,57	53,81	60	19	32	40	-	10	24	0,410
19 L 050	19	6F	ST	57,61	56,84	64	19	32	40	-	10	24	0,450
20 L 050	20	6F	ST	60,64	59,88	66,5	19	32	40	-	10	28	0,500
21 L 050	21	6F	ST	63,67	62,91	70	19	32	45	-	10	28	0,550
22 L 050	22	6F	ST	66,70	65,94	75	19	32	45	-	10	30	0,620
24 L 050	24	6F	ST	72,77	72,00	79	19	32	55	-	10	30	0,680
26 L 050	26	6F	ST	78,83	78,07	86	19	32	58	-	11	30	0,820
28 L 050	28	6F	ST	84,89	84,13	91	19	32	58	-	11	30	0,920
30 L 050	30	6F	ST	90,96	90,20	97	19	32	70	-	11	30	1,100
32 L 050	32	6F	ST	97,02	96,26	102	19	32	70	-	11	30	1,200
36 L 050	36	6F	ST	109,15	108,39	115	19	32	70	-	11	30	1,000
40 L 050	40	6WF	ST	121,28	120,51	128	19	32	70	100	11	30	1,100
44 L 050	44	6WF	ST	133,40	132,64	142	19	32	70	112	11	30	1,200
48 L 050	48	6WF	ST	145,53	144,77	150	19	32	70	124	11	30	1,300
60 L 050	60	6W	GG	181,91	181,15	-	19	42	75	160	14	30	1,300
72 L 050	72	6A	GG	218,30	217,53	-	19	42	75	197	14	30	1,700
84 L 050	84	6A	GG	254,68	253,92	-	19	42	75	233	14	30	1,900
L - Teilung 9,525 mm für Riemenbreite 075													
10 L 075	10	6F	ST	30,32	29,56	37	25	38	20	-	8	13	0,150
12 L 075	12	6F	ST	36,38	35,62	43	25	38	24	-	8	17	0,230
13 L 075	13	6F	ST	39,41	38,65	44	25	38	28	-	8	19	0,260
14 L 075	14	6F	ST	42,45	41,68	48	25	38	28	-	11	20	0,320
15 L 075	15	6F	ST	45,48	44,72	51	25	38	34	-	11	23	0,350
16 L 075	16	6F	ST	48,51	47,75	54	25	38	36	-	11	23	0,420
17 L 075	17	6F	ST	51,54	50,78	57	25	38	36	-	11	24	0,450
18 L 075	18	6F	ST	54,57	53,81	60	25	38	40	-	11	24	0,510
19 L 075	19	6F	ST	57,61	56,84	64	25	38	40	-	11	24	0,570
20 L 075	20	6F	ST	60,64	59,88	66,5	25	38	45	-	11	28	0,630
21 L 075	21	6F	ST	63,67	62,91	70	25	38	45	-	11	28	0,700
22 L 075	22	6F	ST	66,70	65,94	75	25	38	55	-	11	30	0,750
24 L 075	24	6F	ST	72,77	72,00	79	25	38	58	-	11	30	0,850
26 L 075	26	6F	ST	78,83	78,07	86	25	38	58	-	11	30	1,000
28 L 075	28	6F	ST	84,89	84,13	91	25	38	70	-	11	30	1,200
30 L 075	30	6F	ST	90,96	90,20	97	25	38	70	-	11	30	1,400
32 L 075	32	6F	ST	97,02	96,26	102	25	38	70	-	11	30	1,500
36 L 075	36	6F	ST	109,15	108,39	115	25,0	38	70	-	11	32	1,300
40 L 075	40	6WF	ST	121,28	120,51	128	25,0	38	70	100	11	35	1,600

[illegible]

AL = Aluminium ST = Stahl GG = Grauguss **Fertigungstechnische Änderungen vorbehalten.**