


Ausf. 6



Ausf. 6F

Bezeichnung	Anzahl der Zähne	Ausführung	Material	D _p (mm)	D _e (mm)	D _f (mm)	F (mm)	L (mm)	D _m (mm)	Vorbohrung d (mm)	Fertigbohrung d _{max} (mm)	Gewicht (≈kg)
T10 - Teilung 10 mm für Riemenbreite 16 mm												
31 T10 / 12-2	12	6F	AL	38,20	36,35	42	21	31	28	6	16	0,076
31 T10 / 14-2	14	6F	AL	44,56	42,70	48	21	31	32	8	18	0,104
31 T10 / 15-2	15	6F	AL	47,75	45,90	51	21	31	32	8	18	0,116
31 T10 / 16-2	16	6F	AL	50,93	49,10	54	21	31	35	8	20	0,134
31 T10 / 18-2	18	6F	AL	57,29	55,45	60	21	31	40	8	22	0,167
31 T10 / 19-2	19	6F	AL	60,48	58,60	66,5	21	31	44	8	22	0,184
31 T10 / 20-2	20	6F	AL	63,66	61,80	66,5	21	31	46	8	24	0,208
31 T10 / 22-2	22	6F	AL	70,03	68,20	75	21	31	52	8	28	0,253
31 T10 / 24-2	24	6F	AL	76,39	74,55	83	21	31	58	8	30	0,288
31 T10 / 25-2	25	6F	AL	79,58	77,70	83	21	31	60	8	30	0,310
31 T10 / 26-2	26	6F	AL	82,76	80,90	87	21	31	60	8	30	0,357
31 T10 / 27-2	27	6F	AL	85,95	84,10	91	21	31	60	8	30	0,364
31 T10 / 28-2	28	6F	AL	89,12	87,25	93	21	31	60	8	30	0,401
31 T10 / 30-2	30	6F	AL	95,49	93,65	97	21	31	60	8	30	0,441
31 T10 / 32-2	32	6F	AL	101,86	100,00	106	21	31	65	10	32	0,493
31 T10 / 36-2	36	6F	AL	114,59	112,75	119	21	31	70	10	35	0,623
31 T10 / 40-2	40	6F	AL	127,32	125,45	131	21	31	80	10	40	0,767
31 T10 / 44-0	44	6	AL	140,05	138,20	-	21	31	88	10	46	0,993
31 T10 / 48-0	48	6	AL	152,78	150,95	-	21	31	95	16	48	1,090
31 T10 / 60-0	60	6	AL	190,98	189,10	-	21	31	110	16	60	1,710
T10 - Teilung 10 mm für Riemenbreite 25 mm												
40 T10 / 12-2	12	6F	AL	38,20	36,35	42	30	40	28	6	16	0,099
40 T10 / 14-2	14	6F	AL	44,56	42,70	48	30	40	32	8	18	0,134
40 T10 / 15-2	15	6F	AL	47,75	45,90	51	30	40	32	8	18	0,152
40 T10 / 16-2	16	6F	AL	50,93	49,10	54	30	40	35	8	20	0,176
40 T10 / 18-2	18	6F	AL	57,29	55,45	60	30	40	40	8	22	0,224
40 T10 / 19-2	19	6F	AL	60,48	58,65	66,5	30	40	44	8	22	0,247
40 T10 / 20-2	20	6F	AL	63,66	61,80	66,5	30	40	46	8	24	0,276
40 T10 / 22-2	22	6F	AL	70,03	68,20	75	30	40	52	8	28	0,337
40 T10 / 24-2	24	6F	AL	76,39	74,55	83	30	40	58	8	30	0,392
40 T10 / 25-2	25	6F	AL	79,58	77,75	83	30	40	60	8	30	0,422
40 T10 / 26-2	26	6F	AL	82,76	80,90	87	30	40	60	8	30	0,477
40 T10 / 27-2	27	6F	AL	85,95	84,10	91	30	40	60	8	30	0,536
40 T10 / 28-2	28	6F	AL	89,12	87,25	93	30	40	60	8	30	0,540
40 T10 / 30-2	30	6F	AL	95,49	93,65	97	30	40	60	8	30	0,640
40 T10 / 32-2	32	6F	AL	101,86	100,00	106	30	40	65	10	32	0,693
40 T10 / 36-2	36	6F	AL	114,59	112,75	119	30	40	70	10	35	0,873
40 T10 / 40-2	40	6F	AL	127,32	125,45	131	30	40	80	10	40	1,067
40 T10 / 44-0	44	6	AL	140,05	138,20	-	30	40	88	10	46	1,350
40 T10 / 48-0	48	6	AL	152,78	150,95	-	30	40	95	16	48	1,516
40 T10 / 60-0	60	6	AL	190,98	189,10	-	30	40	110	16	60	2,339
T10 - Teilung 10 mm für Riemenbreite 32 mm												
47 T10 / 18-2	18	6F	AL	57,29	55,45	60	37	47	40	10	22	0,253
47 T10 / 19-2	19	6F	AL	60,48	58,65	66,5	37	47	44	10	22	0,286

[illegible]