


Ausf. 6



Ausf. 6F

Bezeichnung	Anzahl der Zähne	Ausführung	Material	D _p (mm)	D _s (mm)	D _i (mm)	F (mm)	L (mm)	D _m (mm)	Vorbohrung d (mm)	Fertigbohrung d _{max} (mm)	Gewicht (≈kg)
T5 - Teilung 5 mm für Riemenbreite 10 mm												
21 T5 / 10-2	10	6F	AL	15,92	15,05	19,5	15	21	8	-	5	0,012
21 T5 / 12-2	12	6F	AL	19,10	18,25	23	15	21	11	-	6	0,016
21 T5 / 14-2	14	6F	AL	22,29	21,45	25	15	21	13	-	8	0,019
21 T5 / 15-2	15	6F	AL	23,88	23,05	28	15	21	16	-	10	0,021
21 T5 / 16-2	16	6F	AL	25,47	24,60	32	15	21	18	-	11	0,025
21 T5 / 18-2	18	6F	AL	28,65	27,80	32	15	21	20	-	12	0,031
21 T5 / 19-2	19	6F	AL	30,25	29,40	36	15	21	20	-	12	0,036
21 T5 / 20-2	20	6F	AL	31,83	31,00	36	15	21	22	-	14	0,038
21 T5 / 22-2	22	6F	AL	35,12	34,25	38	15	21	23	-	15	0,046
21 T5 / 24-2	24	6F	AL	38,21	37,40	42	15	21	24	-	15	0,054
21 T5 / 25-2	25	6F	AL	39,80	39,00	44	15	21	26	-	15	0,058
21 T5 / 26-2	26	6F	AL	41,39	40,60	44	15	21	26	-	16	0,062
21 T5 / 27-2	27	6F	AL	42,98	42,20	48	15	21	30	8	18	0,064
21 T5 / 28-2	28	6F	AL	44,58	43,75	48	15	21	32	8	18	0,071
21 T5 / 30-2	30	6F	AL	47,76	46,95	51	15	21	34	8	18	0,075
21 T5 / 32-2	32	6F	AL	50,94	50,10	54	15	21	38	8	22	0,088
21 T5 / 36-2	36	6F	AL	57,31	56,45	64	15	21	38	8	22	0,114
21 T5 / 40-2	40	6F	AL	63,66	62,85	66,5	15	21	40	8	23	0,138
21 T5 / 42-2	42	6F	AL	66,87	66,00	70	15	21	40	8	24	0,180
21 T5 / 44-0	44	6	AL	70,07	69,20	-	15	21	45	8	26	0,185
21 T5 / 48-0	48	6	AL	76,42	75,55	-	15	21	50	8	28	0,200
21 T5 / 60-0	60	6	AL	95,52	94,65	-	15	21	65	8	35	0,307
T5 - Teilung 5 mm für Riemenbreite 16 mm												
27 T5 / 10-2	10	6F	AL	15,92	15,05	19,5	21	27	8	-	5	0,016
27 T5 / 12-2	12	6F	AL	19,01	18,25	23	21	27	11	-	6	0,022
27 T5 / 14-2	14	6F	AL	22,29	21,45	25	21	27	13	-	8	0,026
27 T5 / 15-2	15	6F	AL	23,88	23,05	28	21	27	16	-	10	0,029
27 T5 / 16-2	16	6F	AL	25,47	24,60	32	21	27	18	-	11	0,035
27 T5 / 18-2	18	6F	AL	28,65	27,80	32	21	27	20	-	12	0,043
27 T5 / 19-2	19	6F	AL	30,25	29,40	36	21	27	20	-	12	0,049
27 T5 / 20-2	20	6F	AL	31,83	31,00	36	21	27	22	-	14	0,053
27 T5 / 22-2	22	6F	AL	35,12	34,25	38	21	27	23	-	15	0,054
27 T5 / 24-2	24	6F	AL	38,21	37,40	42	21	27	24	-	15	0,076
27 T5 / 25-2	25	6F	AL	39,80	39,00	44	21	27	26	-	15	0,081
27 T5 / 26-2	26	6F	AL	41,47	40,60	44	21	27	26	-	16	0,085
27 T5 / 27-2	27	6F	AL	42,98	42,20	48	21	27	30	8	18	0,090
27 T5 / 28-2	28	6F	AL	44,62	43,75	48	21	27	32	8	18	0,092
27 T5 / 30-2	30	6F	AL	47,76	46,95	51	21	27	34	8	18	0,105
27 T5 / 32-2	32	6F	AL	50,94	50,10	54	21	27	38	8	22	0,123
27 T5 / 36-2	36	6F	AL	57,31	56,45	64	21	27	38	8	22	0,160
27 T5 / 40-2	40	6F	AL	63,66	62,85	66,5	21	27	40	8	23	0,193
27 T5 / 42-2	42	6F	AL	66,87	66,00	70	21	27	40	8	24	0,205
27 T5 / 44-0	44	6	AL	70,07	69,20	-	21	27	45	8	26	0,228
27 T5 / 48-0	48	6	AL	76,42	75,55	-	21	27	50	8	28	0,280

[illegible]

AL = Aluminium **Fertigungstechnische Änderungen vorbehalten.**